

Product Summary 19 - HT

19 Sep 2020

Push fit, twin wall, insulated, stainless steel flue system for use on gas, oil and solid fuel appliances.

Midtherm HT is designed for the commercial market serving gas, oil, solid and multifuel installations, peat, wood and other biomass. Midtherm HT has a high temperature negative pressure. HT has a 0.5mm 316L 2B grade stainless steel inner liner with a welded seam and a 0.5mm 304 BA grade stainless steel outer casing with a welded seam. Insulation is 25mm/50mm high density mineral wool.

Available in diameters from 400 to 760 mm - This product is made to order

Maximum operating temperature 450 deg C

Standard finish is: Bright annealed stainless finish

(All products can be powder coated to any BS or RAL colour code)

1 year manufacturer's warranty for all products installed and maintained in accordance with the installation and usage notes.

Suitable for the following Applications:

Ventilation and Extract, Gas, Oil, Solid Fuel, Pellet, Biomass,

It is manufactured using the latest manufacturing and welding technology ensuring high quality and value for money. Lengths and fittings have a quick and easy to use socket and spigot jointing system. Locking bands are used to secure the joint on site.



Notes:

All information is correct at 19 Sep 2020 and subject to change without notice.

All flue system installations, i.e. oil, gas, solid and multi fuel, should be carried out by a suitably qualified installer or Building Control Department permission must be granted. For detailed installation guidelines please refer to: The relevant Te

