

## Product Summary 35b - Midflex 904L

14 Aug 2022

Twin Wall Multifuel Flexible Liner in 904L grade stainless steel.

Midtherm Midflex 904L is a twin wall flexible liner made from 904L grade stainless steel (a high performance austenitic stainless steel) with high levels of chrome, nickel, molybdenum and copper which provide it with the exceptional corrosive resistance.

Available in diameters from 125 to 200 mm - Stocked in sizes from 125 to 200 mm

Maximum operating temperature 600 deg C

Standard finish is: 904 stainless finish

Supplied Fully bubble wrapped and labelled

Midtherm Flue Systems Ltd offer an extended 35 year warranty scheme for the registered Midflex 904L Class 1 flexible liner installations against defects due to faulty manufacture or defective materials when used for its intended purpose subject to the conditions listed in the warranty scheme. If slumbering operation is likely to occur then our 904L product should be used.

Suitable for the following Applications:

Ventilation and Extract, Gas, Oil, Solid Fuel, Pellet, Biomass,

The Midflex 904L is extremely resistant to pitting and crevice corrosion and has very good resistance to stress corrosion cracking.



### Notes:

All information is correct at 14 Aug 2022 and subject to change without notice.

All flue system installations, i.e. oil, gas, solid and multi fuel, should be carried out by a suitably qualified installer or Building Control Department permission must be granted. For detailed installation guidelines please refer to: The relevant Te

### Product Certification:

BS EN 1856-2:2004 & BS EN 1443:2003 / 52022/1

Certificate of Conformity of the Factory  
Production Control / 0086-CPR-597284

